

低温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)
				-20		-25		-30		-35		-40							
				制冷量/输入功率 Cooling Capacity/Power Input (kw)															
EPL-BF -25L	HSN5353 -25 (25HP)	1	35	52.1	19.7	43.2	18.9	35.5	18.1	28.7	14.7	22.7	16.7	80	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	49.9	24.0	41.2	23.1	33.6	22.2	27.0	21.3	21.2	20.5						
			45	46.8	29.3	38.5	28.3	31.0	27.1	24.5	25.9	18.8	24.6						
EPL-BBF2 -50L	HSN5353 -25 (25HP)	2	35	104.2	39.4	86.4	37.8	71.0	36.2	57.4	34.8	45.4	33.4	100	Ø57	Ø133	Ø89	Ø76	3150×1900×1700
			40	99.8	48.0	82.4	46.2	67.2	44.4	54.0	42.6	42.4	41.0						
			45	93.6	58.6	77.0	56.6	62.0	54.2	49.0	51.8	37.6	49.2						
EPL-BBF3 -75L	HSN5353 -25 (25HP)	3	35	156.3	59.1	129.6	56.7	106.5	54.3	86.1	52.2	68.1	50.1	150	Ø57	Ø108 x2	Ø108	Ø89	3950×1900×1750
			40	149.7	72.0	123.6	69.3	100.8	66.6	81.0	63.9	63.6	61.5						
			45	140.4	87.9	115.5	84.9	93.0	81.3	73.5	77.7	56.4	73.8						
EPL-BBF4 -100L	HSN5353 -25 (25HP)	4	35	208.4	78.8	172.8	75.6	142.0	72.4	114.8	69.6	90.8	66.8	200	Ø57	Ø133 x2	Ø133	Ø89	4900×1900×1750
			40	199.6	96.0	164.8	92.4	134.4	88.8	96.0	85.2	84.8	82.0						
			45	187.2	117.2	154.0	113.2	124.0	108.4	98.0	103.6	75.2	98.4						
EPL-BF -30L	HSN5363 -30 (30HP)	1	35	60.8	23.0	50.6	21.9	41.6	20.9	33.6	20.0	26.7	19.1	80	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	58.1	27.8	48.2	26.7	39.4	25.6	31.7	24.5	25.0	23.5						
			45	54.5	33.9	44.9	32.6	36.4	31.3	28.9	30.0	22.4	28.6						
EPL-BBF2 -60L	HSN5363 -30 (30HP)	2	35	121.6	46.0	101.2	43.8	83.2	41.8	67.2	40.0	53.4	38.2	150	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	116.2	55.6	96.4	53.4	78.8	51.2	63.4	49.0	50.0	47.0						
			45	109.0	67.8	89.8	65.2	72.8	62.6	57.8	60.0	44.8	57.2						
EPL-BBF3 -90L	HSN5363 -30 (30HP)	3	35	182.4	69.0	151.8	65.7	124.8	62.7	100.8	60.0	80.1	57.3	200	Ø57	Ø108 x2	Ø108	Ø89	4100×1950×1750
			40	174.3	83.4	144.6	80.1	118.2	76.8	95.1	73.5	75.0	70.5						
			45	163.5	101.7	134.7	97.8	109.2	93.9	86.7	90.0	67.2	85.8						
EPL-BBF4 -120L	HSN5363 -30 (30HP)	4	35	243.2	92.0	202.4	87.6	166.4	83.6	134.4	80.0	106.8	76.4	250	Ø57	Ø133 x2	Ø133	Ø89	4950×1950×1750
			40	232.4	111.2	192.8	150.6	157.6	102.4	126.8	98.0	100.0	94.0						
			45	218.0	135.6	179.6	130.4	145.6	125.2	115.6	120.0	89.6	114.4						
EPL-BF -40L	HSN6451 -40 (40HP)	1	35	70.1	26.3	58.3	25.2	47.8	24.2	38.6	23.3	30.6	22.4	100	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	67.0	31.9	55.5	30.8	45.3	29.7	36.4	28.6	28.6	27.5						
			45	62.9	38.9	51.7	37.6	41.8	36.2	33.0	34.8	25.4	33.2						
EPL-BBF2 -80L	HSN6451 -40 (40HP)	2	35	140.2	52.6	116.6	50.4	95.6	48.4	77.2	46.6	61.2	44.8	200	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	134.0	63.8	111.0	61.6	90.6	59.4	72.8	57.2	57.2	55.0						
			45	125.8	116.7	103.4	75.2	83.6	72.4	66.0	69.6	50.8	66.4						
EPL-BBF3 -120L	HSN6451 -40 (40HP)	3	35	210.3	78.9	174.9	75.6	143.4	72.6	115.8	69.9	91.8	67.2	250	Ø57	Ø108 x2	Ø108	Ø89	4100×1950×1750
			40	201.0	95.7	166.5	92.4	135.9	89.1	109.2	85.8	85.8	82.5						
			45	188.7	116.7	155.1	112.8	125.4	108.6	99.0	104.4	76.2	99.6						
EPL-BBF4 -160L	HSN6451 -40 (40HP)	4	35	280.4	105.2	233.2	104.8	191.2	96.8	154.4	93.2	122.4	89.6	300	Ø76	Ø133 x2	Ø133	Ø108	4950×1950×1800
			40	268.0	127.6	222.0	123.2	181.2	118.8	145.6	114.4	114.4	110.0						
			45	251.6	154.4	206.8	150.4	167.2	144.8	132.0	139.2	101.6	132.8						

低温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)
				-20		-25		-30		-35		-40							
				制冷量/输入功率 Cooling Capacity/Power Input (kw)															
EPL-BF -50L	HSN6461 -50 (50HP)	1	35	83.2	33.2	66.0	32.1	54.1	30.8	43.7	29.6	34.6	28.5	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	79.2	37.7	64.2	35.3	52.5	34.0	42.3	32.8	33.3	31.5						
			45	73.9	41.0	62.0	38.9	50.6	37.6	40.5	36.3	31.7	34.9						
EPL-BBF2 -100L	HSN6461 -50 (50HP)	2	35	166.4	66.4	132.0	64.2	108.2	61.6	87.4	59.2	69.2	57.0	200	Ø57	Ø133	Ø89	Ø76	3150×1900×1700
			40	158.4	75.4	128.4	70.6	105.0	68.0	84.6	65.6	66.6	63.0						
			45	147.8	82.0	124.0	77.8	101.2	75.2	81.0	72.6	63.4	69.8						
EPL-BBF3 -150L	HSN6461 -50 (50HP)	3	35	249.6	99.6	198.0	96.3	162.3	92.4	131.1	88.8	103.8	85.5	300	Ø57	Ø108 x2	Ø108	Ø89	3950×1900×1750
			40	237.6	113.1	192.6	105.9	157.5	102.0	126.9	98.4	99.9	94.5						
			45	221.7	123.0	186.0	116.7	151.8	112.8	121.5	108.9	95.1	104.7						
EPL-BBF4 -200L	HSN6461 -50 (50HP)	4	35	332.8	132.8	264.0	128.4	216.4	123.2	174.8	118.4	138.4	114.0	400	Ø57	Ø133 x2	Ø133	Ø89	4900×1900×1750
			40	316.8	150.8	256.8	141.2	210.0	136.0	169.2	131.2	133.2	126.0						
			45	295.6	164.0	248.0	155.6	202.4	150.4	162.0	145.2	126.8	139.6						
EPL-BF -60L	HSN7451 -60 (60HP)	1	35	95.2	40.0	80.0	38.8	65.9	37.3	52.7	36.0	41.2	34.8	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	92.7	44.7	74.8	43.2	63.6	41.7	50.7	40.3	39.5	39.0						
			45	90.0	49.6	75.4	48.1	61.0	46.6	48.4	45.0	37.4	43.5						
EPL-BBF2 -120L	HSN7451 -60 (60HP)	2	35	190.4	80.8	160.0	77.6	131.8	74.6	105.4	72.0	82.4	69.6	250	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	185.4	89.4	156.8	86.4	127.2	83.4	101.4	80.6	79.0	78.0						
			45	180.0	99.2	150.8	96.2	122.0	93.2	96.8	90.0	74.8	87.0						
EPL-BBF3 -180L	HSN7451 -60 (60HP)	3	35	285.6	120.0	240.0	116.4	197.7	111.9	158.1	108.0	123.6	104.4	350	Ø57	Ø108 x2	Ø108	Ø89	4100×1950×1750
			40	278.1	134.1	235.2	129.6	190.8	125.1	152.1	120.9	118.5	117.0						
			45	270.0	148.8	226.2	144.3	183.0	139.8	145.2	135.0	112.2	130.5						
EPL-BBF4 -240L	HSN7451 -60 (60HP)	4	35	380.8	160.0	320.0	155.2	263.6	149.2	210.8	144.0	164.8	139.2	400	Ø57	Ø133 x2	Ø133	Ø89	4950×1950×1750
			40	370.8	178.8	313.6	172.8	254.4	166.8	202.8	161.2	158.0	156.0						
			45	360.0	198.4	301.6	192.4	244.0	186.4	193.6	180.0	149.6	174.0						
EPL-BF -70L	HSN7461 -70 (70HP)	1	35	107.6	44.8	91.1	43.3	74.6	41.8	60.2	40.4	47.6	39.0	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	105.0	49.3	88.5	47.8	72.3	46.2	58.1	44.7	45.8	43.1						
			45	91.4	54.2	80.5	52.7	69.6	51.0	55.7	49.3	48.5	47.5						
EPL-BBF2 -140L	HSN7461 -70 (70HP)	2	35	215.2	89.6	182.2	86.6	149.2	83.6	120.4	80.8	95.2	78.0	250	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	210.0	98.6	177.0	95.6	144.6	92.4	116.2	89.4	91.6	86.2						
			45	182.8	108.4	171.0	105.4	139.2	102.0	111.4	98.6	87.0	95.0						
EPL-BBF3 -210L	HSN7461 -70 (70HP)	3	35	322.8	133.4	273.3	129.9	223.8	125.4	180.6	121.2	142.8	117.0	350	Ø57	Ø108 x2	Ø108	Ø89	4100×1950×1750
			40	315.0	147.9	265.5	143.1	216.9	138.6	174.3	134.1	137.4	129.3						
			45	274.2	162.6	256.5	138.1	208.8	153.0	167.1	147.9	130.5	142.5						
EPL-BBF4 -280L	HSN7461 -70 (70HP)	4	35	430.4	179.2	364.4	173.2	298.4	167.2	240.8	161.6	190.4	156.0	500	Ø76	Ø133 x2	Ø133	Ø108	4950×1950×1800
			40	420.0	197.2	354.0	190.8	289.2	184.8	232.4	178.8	183.2	172.4						
			45	365.6	216.8	342.0	210.8	278.4	204.0	222.8	197.2	174.0	190.0						

低温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)
				-20		-25		-30		-35		-40							
				制冷量/输入功率 Cooling Capacity/Power Input (kw)															
EPL-BF-75L	HSN7461-75 (75HP)	1	35	116.2	48.6	98.5	46.7	80.8	44.8	65.3	43.1	51.8	41.5	200	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	112.9	52.8	95.6	51.2	78.3	49.8	63.1	47.6	49.8	45.9						
			45	109.1	58.3	92.2	56.4	75.3	54.5	60.4	52.7	47.4	50.8						
EPL-BBF2-150L	HSN7461-75 (75HP)	2	35	232.4	97.2	197.0	93.4	161.6	89.6	130.6	86.2	103.6	83.0	250	Ø57	Ø133	Ø89	Ø76	3150×1900×1700
			40	225.8	105.6	191.2	102.4	156.6	98.8	126.2	95.2	99.6	91.8						
			45	218.2	116.6	184.4	112.8	150.6	109.0	120.8	150.4	94.8	101.6						
EPL-BBF3-225L	HSN7461-75 (75HP)	3	35	348.6	145.8	295.5	140.1	242.4	134.4	195.9	129.3	155.4	124.5	350	Ø57	Ø108×2	Ø108	Ø89	3950×1900×1750
			40	338.7	158.4	286.8	153.6	234.9	148.2	189.3	142.8	149.4	137.7						
			45	327.3	174.9	276.6	169.2	225.9	163.5	181.2	158.1	142.2	152.4						
EPL-BBF4-300L	HSN7461-75 (75HP)	4	35	464.8	194.4	394.0	186.8	323.2	179.2	261.2	173.4	207.2	166.0	400	Ø57	Ø133×2	Ø133	Ø89	4900×1900×1750
			40	451.6	211.2	382.4	204.8	313.2	197.6	252.4	190.4	199.2	183.6						
			45	436.4	233.2	368.8	225.6	301.2	218.0	241.6	210.8	189.6	203.2						
EPL-BF-125L	HSN8571-125 (125HP)	1	35	194.9	77.9	165.6	74.5	136.3	71.1	100.7	67.9	88.5	64.7	250	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	189.5	85.7	160.7	82.0	131.9	78.3	106.6	74.6	84.7	70.9						
			45	183.2	94.2	154.9	90.5	126.6	86.5	101.8	83.2	80.2	77.8						
EPL-BBF2-250L	HSN8571-125 (125HP)	2	35	389.8	155.8	311.2	149.0	272.6	144.2	221.4	135.8	177.0	128.4	400	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	379.0	171.4	321.4	164.0	263.8	156.6	313.2	149.2	169.4	141.8						
			45	366.4	188.4	39.8	181.0	253.2	173.0	203.6	164.6	160.4	155.6						
EPL-BBF3-375L	HSN8571-125 (125HP)	3	35	584.7	233.7	496.8	223.5	408.9	213.3	332.1	203.7	265.5	194.1	500	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750
			40	568.5	257.1	482.1	246.0	395.7	234.9	319.8	223.8	254.1	212.7						
			45	549.6	282.6	164.7	217.5	379.8	259.5	305.4	246.9	240.6	233.4						
EPL-BBF4-500L	HSN8571-125 (125HP)	4	35	779.6	311.6	662.4	298.0	545.2	284.4	442.8	271.6	354.0	258.8	800	Ø57	Ø133×2	Ø133	Ø89	4950×1950×1750
			40	758.0	342.8	642.8	328.0	527.6	313.2	426.4	298.4	338.8	283.6						
			45	732.8	376.8	619.6	362.0	506.4	346.0	407.2	329.2	320.8	311.2						
EPL-BF-1600L	HSN8591-160 (160HP)	1	35	247.5	102.0	210.0	98.7	172.3	95.3	139.0	91.7	111.0	88.1	300	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	248.0	113.0	204.0	109.2	167.2	105.4	134.8	101.5	106.9	97.3						
			45	232.8	125.4	197.0	121.1	161.2	116.8	129.5	112.3	102.0	107.4						
EPL-BBF2-320L	HSN8591-160 (160HP)	2	35	495.0	204.0	420.0	197.4	344.6	190.6	278.0	183.4	222.0	176.2	500	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	481.6	226.0	408.0	218.4	335.0	218.0	269.6	203.0	213.8	194.6						
			45	465.6	250.8	394.0	242.2	322.4	233.6	259.0	224.6	204.0	214.8						
EPL-BBF3-480L	HSN8591-160 (160HP)	3	35	742.5	306.0	630.0	296.1	516.9	285.9	417.0	275.1	333.0	264.3	600	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750
			40	722.4	339.0	612.0	327.6	502.5	316.2	404.4	304.5	320.7	291.9						
			45	698.4	376.2	591.0	363.3	483.6	350.4	388.5	336.9	306.0	322.2						
EPL-BBF4-640L	HSN8591-160 (160HP)	4	35	990.0	408.0	840.0	394.8	689.2	381.2	556.0	366.8	444.0	352.4	800	Ø76	Ø133×2	Ø133	Ø108	4950×1950×1800
			40	963.2	452.0	816.0	436.8	670.0	421.6	539.2	406.0	427.6	389.2						
			45	931.2	501.6	788.0	484.4	644.8	467.2	518.0	449.2	408.0	429.6						

高温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)
				-15		-10		-5		0		5							
				制冷量/输入功率 Cooling Capacity/Power Input (kw)															
EPL-BF-40H	HSK5363-40 (40HP)	1	35	61.7	21.4	75.0	22.2	90.2	23.0	107.6	23.8	127.4	24.5	100	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	54.3	25.7	66.7	26.3	80.9	27.0	97.1	27.8	115.5	28.8						
			45	46.4	31.3	57.7	31.7	70.7	32.3	85.5	33.0	102.5	33.7						
EPL-BBF2-80H	HSK5363-40 (40HP)	2	35	123.4	42.8	150.0	44.4	180.4	46.0	215.2	47.6	254.8	49.0	200	Ø57	Ø133	Ø89	Ø76	3150×1900×1700
			40	108.6	51.4	133.4	52.6	161.8	54.0	194.2	55.6	231.0	57.6						
			45	92.8	62.2	115.4	63.4	141.4	64.6	171.0	66.0	205.0	67.4						
EPL-BBF3-120H	HSK5363-40 (40HP)	3	35	185.1	64.2	255.0	66.6	270.6	69.0	322.8	71.4	382.2	73.5	250	Ø57	Ø108×2	Ø108	Ø89	3950×1900×1750
			40	162.9	77.1	200.1	78.9	242.7	81.0	291.3	83.4	346.5	86.4						
			45	139.2	93.9	173.1	95.1	212.1	96.9	256.5	99.0	307.5	101.1						
EPL-BBF4-160H	HSK5363-40 (40HP)	4	35	246.8	85.6	300.0	88.8	360.8	92.0	430.4	95.2	504.6	98.0	300	Ø57	Ø133×2	Ø133	Ø89	4900×1900×1750
			40	217.2	102.8	266.8	105.2	323.6	108.0	388.4	111.2	462.0	115.2						
			45	185.6	125.2	230.8	126.8	282.8	129.2	342.0	132.0	410.0	134.8						
EPL-BF-50H	HSK6451-50 (50HP)	1	35	71.6	24.5	87.5	24.8	105.7	25.3	126.7	25.7	150.6	26.3	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	62.8	30.1	77.3	30.2	94.0	30.4	113.3	30.8	135.4	31.6						
			45	53.0	37.1	66.1	37.1	81.3	37.1	98.9	37.2	119.1	37.5						
EPL-BBF2-100H	HSK6451-50 (50HP)	2	35	143.2	49.0	175.0	49.6	211.4	50.6	253.4	51.4	301.2	52.6	200	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	125.6	60.2	154.6	60.4	188.0	60.8	226.6	61.6	270.8	63.2						
			45	106.0	74.2	132.2	74.2	162.6	74.1	197.8	74.4	238.2	75.0						
EPL-BBF3-150H	HSK6451-50 (50HP)	3	35	214.8	73.5	262.5	74.4	317.1	77.1	380.1	77.1	451.8	78.9	300	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750
			40	188.4	90.3	231.9	90.6	282.2	91.2	339.9	92.4	406.2	94.8						
			45	159.0	111.3	198.3	111.3	243.9	111.3	296.7	111.6	357.3	115.2						
EPL-BBF4-200H	HSK6451-50 (50HP)	4	35	186.4	98.0	350.0	99.2	421.8	101.2	506.8	102.8	602.4	105.2	400	Ø57	Ø133×2	Ø133	Ø89	4950×1950×1750
			40	251.2	120.4	309.2	120.8	376.0	121.6	453.2	123.2	541.6	126.4						
			45	212.0	148.4	264.4	148.4	325.2	148.4	395.6	148.8	476.4	150.0						
EPL-BF-60H	HSK6461-60 (60HP)	1	35	86.5	30.0	105.2	31.1	126.5	32.2	150.9	33.3	178.6	34.4	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650
			40	76.2	36.1	93.6	36.9	113.5	37.9	136.2	39.0	162.0	40.3						
			45	65.0	43.8	80.9	44.5	99.1	45.3	119.9	46.2	143.1	47.3						
EPL-BBF2-120H	HSK6461-60 (60HP)	2	35	173.0	60.0	210.4	62.2	253.0	64.6	301.8	66.6	357.2	68.6	250	Ø57	Ø133	Ø108	Ø76	3200×1950×1700
			40	152.4	72.2	187.2	73.8	227.0	75.8	272.4	78.0	324.0	80.6						
			45	130.0	87.6	161.8	89.0	198.2	90.6	239.8	92.4	287.4	94.6						
EPL-BBF3-180H	HSK6461-60 (60HP)	3	35	259.5	90.0	315.6	93.3	379.5	96.6	452.7	99.9	535.8	103.2	350	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750
			40	228.6	108.3	280.8	110.7	340.5	113.7	408.6	117.0	486.0	120.9						
			45	195.0	131.4	242.7	133.5	297.3	135.9	359.7	138.6	431.1	141.9						
EPL-BBF4-240H	HSK6461-60 (60HP)	4	35	346.0	120.0	420.8	124.4	506.0	128.8	603.6	133.2	714.4	137.6	400	Ø76	Ø133×2	Ø133	Ø108	4950×1950×1800
			40	304.8	144.4	374.4	147.6	454.0	151.6	544.8	156.0	648.0	161.2						
			45	260.0	175.2	323.6	178.0	396.4	181.2	479.6	184.8	574.8	189.2						

高温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)															
				-15					-10											-5					0					5				
				制冷量/输入功率 Cooling Capacity/Power Input (kw)																														
EPL-BF-740H	HSK7451-70 (70HP)	1	35	106.4	31.6	129.6	36.0	136.4	36.0	187.2	35.9	222.5	35.7	150	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	94.3	45.0	115.8	45.0	140.6	45.0	169.2	45.0	201.9	45.0																					
			45	78.4	56.0	98.1	55.9	121.0	55.7	147.2	55.6	177.3	55.4																					
EPL-BBF2-140H	HSK7451-70 (70HP)	2	35	212.8	72.2	259.2	72.0	312.8	72.0	374.4	71.8	445.0	71.4	300	Ø57	Ø133	Ø89	Ø76	3150×1900×1700															
			40	188.6	90.0	231.6	90.0	281.2	90.0	338.4	90.0	403.8	90.0																					
			45	156.8	112.0	196.2	111.8	242.0	111.4	244.4	111.2	354.6	110.8																					
EPL-BBF3-210H	HSK7451-70 (70HP)	3	35	319.2	108.3	388.8	108.0	469.2	108.0	561.6	107.7	667.5	107.1	400	Ø57	Ø108×2	Ø108	Ø89	3950×1900×1750															
			40	282.9	135.0	347.4	135.0	421.8	135.0	507.6	135.0	605.7	135.0																					
			45	235.2	168.0	294.3	167.7	363.0	167.1	441.6	166.8	531.9	166.2																					
EPL-BBF4-280H	HSK7451-70 (70HP)	4	35	425.6	144.4	518.4	144.0	625.6	144.0	748.8	143.6	890.0	142.8	500	Ø57	Ø133×2	Ø133	Ø89	4900×1900×1750															
			40	377.2	180.0	463.2	180.0	562.4	180.0	676.8	180.0	807.6	180.0																					
			45	313.6	224.0	392.4	223.6	404.0	222.8	588.8	222.4	709.2	221.6																					
EPL-BF-80H	HSK7461-80 (80HP)	1	35	119.3	39.4	145.6	40.0	175.9	40.6	210.7	41.4	250.4	42.3	200	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	104.8	48.5	128.8	48.6	156.7	48.9	188.7	49.6	225.4	50.9																					
			45	88.7	59.7	110.5	59.7	135.8	59.8	165.0	59.9	198.5	60.3																					
EPL-BBF2-160H	HSK7461-80 (80HP)	2	35	238.6	78.8	291.2	80.0	351.8	81.2	421.4	82.8	500.8	84.6	300	Ø57	Ø133	Ø108	Ø76	3200×1950×1700															
			40	209.6	97.0	257.6	97.2	313.4	97.8	377.4	99.2	460.8	101.8																					
			45	177.4	119.4	221.0	119.4	217.6	119.6	330.0	119.8	397.0	120.6																					
EPL-BBF3-240H	HSK7461-80 (80HP)	3	35	357.9	118.2	438.8	120.0	527.7	148.0	632.1	124.2	751.2	126.9	400	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750															
			40	314.4	145.5	386.4	145.8	470.1	146.7	566.1	148.8	676.2	152.7																					
			45	266.1	179.1	331.5	179.1	407.4	179.4	495.0	179.7	595.5	180.9																					
EPL-BBF4-320H	HSK7461-80 (80HP)	4	35	477.2	157.6	582.4	160.0	703.6	162.4	842.8	165.6	1001.6	169.2	500	Ø57	Ø133×2	Ø133	Ø89	4950×1950×1750															
			40	419.2	194.0	515.2	194.4	626.8	195.6	754.8	198.4	901.6	203.6																					
			45	354.8	238.8	442.0	238.8	543.2	239.2	660.0	239.6	794.0	241.2																					
EPL-BF-90H	HSK7471-90 (90HP)	1	35	131.2	44.1	159.4	45.6	191.7	47.2	288.6	48.9	270.6	50.4	200	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	115.7	52.9	142.0	54.1	172.1	55.6	206.5	57.3	245.6	59.2																					
			45	99.0	64.3	123.0	65.2	150.6	66.4	182.1	67.8	218.1	69.3																					
EPL-BBF2-180H	HSK7471-90 (90HP)	2	35	262.4	88.2	318.8	91.2	383.4	94.4	457.2	97.8	541.2	100.8	350	Ø57	Ø133	Ø108	Ø76	3200×1950×1700															
			40	231.4	105.8	284.0	108.2	344.2	111.2	413.0	114.6	491.2	118.4																					
			45	198.0	128.6	246.0	130.4	301.2	132.8	364.2	135.6	436.2	138.6																					
EPL-BBF3-270H	HSK7471-90 (90HP)	3	35	393.6	137.3	478.2	136.8	575.1	141.6	685.8	146.7	811.8	151.2	400	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750															
			40	347.1	158.7	426.0	162.5	516.3	166.8	619.5	171.9	736.8	171.6																					
			45	297.0	192.0	369.0	1195.6	451.8	199.2	546.3	203.4	654.3	207.9																					
EPL-BBF4-360H	HSK7471-90 (90HP)	4	35	524.8	176.4	637.6	182.4	766.8	188.8	914.4	195.6	1082.4	201.6	500	Ø76	Ø133×2	Ø133	Ø108	4950×1950×1800															
			40	462.8	211.6	568.0	216.4	638.4	222.4	826.0	229.2	982.4	236.8																					
			45	396.0	257.2	492.0	260.8	620.4	265.6	728.4	271.2	872.4	277.2																					

高温机组

机组型号 Unit Model	压缩机 型号 Com. Model (比泽尔)	压缩机 数量 Com. Quantity	冷凝温度 Condensing temp. (°C)	蒸发温度 Evaporation Temp. (°C)										储液器 Reservoir (L)	供液管 接口 Supply pipe (mm)	吸气管 接口 Suction pipe (mm)	排气管 接口 Gas Outlet pipe (mm)	回液管 接口 liquid inletpipe (mm)	外形尺寸 Dimension (mm) (L×W×H)															
				-15					-10											-5					0					5				
				制冷量/输入功率 Cooling Capacity/Power Input (kw)																														
EPL-BF-110H	HSK8551-110 (110HP)	1	35	166.9	54.2	203.2	54.1	245.2	54.1	293.5	53.9	348.7	53.7	250	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	147.9	67.6	181.6	67.60	220.5	67.6	265.2	67.6	316.4	67.6																					
			45	123.3	84.2	154.2	84.0	190.0	83.8	231.1	83.5	278.2	83.2																					
EPL-BBF2-220H	HSK8551-110 (110HP)	2	35	333.8	108.4	406.4	108.2	490.4	180.2	587.0	107.8	691.4	107.4	400	Ø57	Ø133	Ø89	Ø76	3150×1900×1700															
			40	295.8	135.2	363.2	135.2	441.0	135.2	530.4	135.2	632.8	135.2																					
			45	246.6	168.4	308.4	168.0	380.0	167.6	462.2	167.0	556.4	166.4																					
EPL-BBF3-330H	HSK8551-110 (110HP)	3	35	500.7	162.6	609.6	162.3	735.6	162.3	880.5	161.76	1046.1	161.1	500	Ø57	Ø108×2	Ø108	Ø89	3950×1900×1750															
			40	443.7	202.8	544.8	202.8	661.5	202.8	795.6	202.8	949.2	202.8																					
			45	369.9	252.6	462.6	252.0	510.0	251.4	693.3	250.5	834.6	249.6																					
EPL-BBF4-440H	HSK8551-110 (110HP)	4	35	667.6	216.8	812.8	216.4	980.8	216.4	1174.0	215.6	1394.8	214.8	600	Ø57	Ø89	Ø133	Ø89	4900×1900×1750															
			40	591.6	270.4	726.4	270.4	882.0	270.4	1060.8	270.4	1265.6	270.4																					
			45	493.2	336.8	616.8	336.0	760.0	335.2	924.4	334.0	1117.8	332.8																					
EPL-BF-125H	HSK8561-125 (125HP)	1	35	188.5	59.7	230.1	66.6	277.9	61.5	332.8	62.7	395.5	64.0	250	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	165.8	73.4	203.8	73.6	244.7	74.1	298.2	75.2	356.1	77.0																					
			45	140.6	90.5	175.0	90.5	214.9	90.5	261.0	90.8	314.0	91.4																					
EPL-BBF2-250H	HSK8561-125 (125HP)	2	35	377.0	119.4	460.2	121.2	555.8	123.0	665.6	125.4	791.0	128.0	500	Ø57	Ø133	Ø108	Ø76	3200×1950×1700															
			40	331.6	146.8	407.6	147.2	495.4	148.2	596.4	150.4	712.2	154.0																					
			45	281.2	181.0	350.0	181.0	429.8	181.0	522.0	181.6	628.0	182.8																					
EPL-BBF3-375H	HSK8561-125 (125HP)	3	35	565.5	179.1	690.3	181.8	833.7	184.5	998.4	188.1	1186.5	192.0	800	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750															
			40	497.4	220.2	611.4	220.8	743.1	222.3	984.6	225.6	1065.3	231.0																					
			45	421.8	271.5	525.0	271.5	644.7	271.5	783.0	272.4	942.0	274.2																					
EPL-BBF4-500H	HSK8561-125 (125HP)	4	35	754.0	238.8	920.4	242.4	1111.6	246.0	1531.2	250.8	1582.0	256.0	500	Ø57	Ø133×2	Ø133	Ø89	4950×1950×1750															
			40	663.2	293.6	815.2	294.4	990.8	296.4	1192.8	300.8	1424.4	308.0																					
			45	562.4	362.0	700.0	362.0	859.6	362.0	1044.0	363.2	1256.0	365.8																					
EPL-BF-140L	HSK8571-140 (140HP)	1	35	214.4	68.6	261.0	71.1	314.6	73.8	376.1	76.5	446.3	79.1	200	Ø28	Ø89	Ø76	Ø28	2850×1800×1650															
			40	191.1	82.5	234.1	84.3	283.7	86.6	340.6	89.5	405.6	92.8																					
			45	163.8	100.9	203.4	102.3	248.8	104.2	301.0	106.4	360.4	108.9																					
EPL-BBF2-280H	HSK8571-140 (140HP)	2	35	428.8	137.2	522.0	142.2	629.2	147.6	752.2	153.0	892.6	158.2	350	Ø57	Ø133	Ø108	Ø76	3200×1950×1700															
			40	382.2	165.0	468.2	168.6	567.4	173.2	681.2	179.0	811.2	185.6																					
			45	327.6	201.8	406.8	204.6	497.6	208.4	602.0	212.8	720.8	217.8																					
EPL-BBF3-420H	HSK8571-140 (140HP)	3	35	643.2	205.8	783.0	213.3	943.8	221.4	1128.3	229.5	1338.9	237.3	400	Ø57	Ø108×2	Ø108	Ø89	4100×1950×1750															
			40	573.3	247.5	702.3	252.9	851.1	259.8	1021.8	268.5	1216.8	278.4																					
			45	491.4	302.7	610.2	306.9	746.4	312.6	903.0	319.2	1081.2	326.7																					
EPL-BBF4-560H	HSK8571-140 (140HP)	4	35	857.6	274.4	1044.4	284.4	1258.4	295.2	1504.4	306.0	1785.2	316.4	500	Ø76	Ø133×2	Ø133	Ø108	4950×1950×1800															
			40	764.4	330.0	936.4	337.2	1134.8	346.4	1362.4	358.0	1622.4	435.6																					
			45	655.2	403.6	813.6	409.2	995.2	416.8	1204.0	425.6	1441.6	435.6																					